STATE WILLIAM STATE OF THE STAT

ROMBLON STATE UNIVERSITY

BIDS AND AWARDS COMMITTEE
Community Outreach Center, RSU-Main Campus, Liwanag, Odiongan, Romblon 5503

Community Outreach Center, RSU-Main Campus, Liwanag, Odiongan, Romblon 5505 Telephone: (042) 567-5952 Email: bac@rsu.edu.ph Website: rsu.edu.ph



TECHNICAL SPECIFICATIONS

Solicitation No. RSU-2023-05-041 ABC: PhP1,808,145.00 QTY: 147

Procurement of Office and ICT Equipment and Supplies for the Different Units of Romblon State University

Units of Rombion State University						
ITEM NO.	UNIT	ITEM DESCRIPTION	QTY	STATEMENT OF COMPLIANCE		
1	unit	High Speed HDMI to HDMI cable digital video with Audio (M/M), Black (15m)	8			
2	unit	Heavy Duty Laminating Machine (13", 4 Rollers, A3 size)	1			
3	unit	Rechargeable Valve Regulated Lead Acid Battery (VRLA); NPW36-12; 12 volts 36 Watts	10			
4	unit	Desktop Computer; Processor: 10th Generation (Comet Lake) 8 cores & 16 Threads 2.9 Ghz Clock Speed 4.8 Ghz Maximum Turbo Frequency LGA 1200 Socket Dual-Channel DDR4-2933 Memory Intel Optane Memory Support Motherboard: Intel B560 (LGA 1200) PCIe 4.0 two M.2 slots 8 power stages Intel 1 Gb Ethernet Display Port Dual HDMI rear USB 3.2 Gen Type-C V-M.2 Key E slot for Wi-Fi Aura Sync Addressable RGB MATX motherboard Memory: 16 GB DDR4 5000 MHz Storage: 500GB SSD Up to 560 MB/s sequential read and 530MB/s write Storage: 500 GB SSD Up to 560 MB/s sequential read and 530 MB/s write GPU: Radeon RX 6500 XT PCI Express 4.0 OpenGL®4.6 Video Memory 4GB GDDR6 Casing: Corsair 5000D with 600 watts power supply for fan Keyboard and Mouse: MasterSet MS120	2			

STATE UNITED STATE

ROMBLON STATE UNIVERSITY

BIDS AND AWARDS COMMITTEE



		Display: at least 19" full HD Display		
		with HDMI, DVI port		
		AVR: 500 watts		
5	Unit	All in One MULTI-FUNCTIONAL	2	
		BORDERLESS PHOTO L850 Printer,		
		Print Method: On-demand ink jet		
		(piezoelectric)		
		Nozzle Configuration: 90 nozzles, each		
		color (Cyan, Light Cyan, Magenta, Light		
		Magenta, Yellow, Black)		
		Print Direction: Bi-direction printing,		
		Unidirectional printing,		
		Maximum Resolution: 5760x1440 dpi		
		(with Variable-sized Droplet Technology)		
		Minimum Ink Droplet Volume: 1.5pl		
6	piece	Wi-Fi Dongle Dual-Band 802.11ac,	5	
		Frequency: 2Ghz		
		Signal Rate: 600Mbps(2.4Ghz),		
		1,300Mbps(5Ghz)		
7	unit	Air Conditioner, 2.5HP Split Type	1	
8	unit	Printer, ADF, color 1.44" LCD	1	
		display, Maximum speed 33 ppm in		
		black and 15 ppm in color (draft)†. Up		
		to 10 ppm in black and 5 ppm in color		
		(ISO), With maximum resolution of		
		1200 x 2400 dpi., Print 100, Borderless		
		printing - 3.5×5 inches (9 cm x 13 cm),		
		4 x 6 inches (10 cm x 15 cm). Wireless		
		printing4 - Wi-Fi Direct® and Ethernet		
		for work groups. Dimensions:Open:		
		14.8 x 22.8 x 10 inches (375 x 578 x		
		253 mm)		
		Closed: 14.8 x 13.7 x 9.3 inches (375		
		mm x 347 mm x 237 mm),		
		Weight:11 lb (5 kg) excludes inks and		
		cables		
9	set	Stand Fan Power;	3	
		Consumption (W) 65; Fan Features Oscillating;	-	
		Fan Blade Materials Metal; Number of Blades:		
		3; Blade Side (inches): 16		
		, , , , , , , , , , , , , , , , , , , ,		

STATE UNITED STATE OF THE PRINTED STATE OF THE PRIN

ROMBLON STATE UNIVERSITY

BIDS AND AWARDS COMMITTEE



10	unit	LCD - EB-X41 XGA 3LCD Technology, RGB Liquid Crystal Shutter 3,600 Lumens Multimedia Projector, Image• Colour Light Output:• White Light Output: • Resolution:• Contrast Ratio: • Lamp: • Keystone Correction:• Colour Reproduction:• Aspect Ratio: • Light source:, Optical• Projection Ratio: • Zoom: • Image Size: • Projection Distance Wide/Tele: • Projection Lens F Number:• Focal Distance:• Focus: • Offset: Connectivity• USB Display Function:• Interfaces:• Epson iProjection App:, Advanced Features• Security: • 3D:• Features: • Video Colour Modes: General• Energy Use:• Product dimensions: • Product weight:• Noise Level: • Loudspeaker: • Colour:	2	
11	piece	USB 64 gb Available capacities: 64 GB, Performance/speed: Read speeds up to 80MB/s** Dimensions: 2.24" x 0.84" x 0.43" (56.8 mm x 21.3 mm x 10.8 mm), Operating temperature: 32° - 113° F (0° - 45° C), Storage temperature: 50° - 158° F (-10° - 70° C) Compatibility: USB 3.0 and USB 2.0	4	
12	set	Glass board Magnetic Dry Erase 60" W	2	
13	unit	x 48" H, Magnetic Dry Erase Printer 3 in 1 Print Method: inkjet (piezoelectric) printer Language: ESC/P-R, ESC/P Raster Nozzle Configuration: 180 x 1 Nozzles Black, 59 x 1nozzles per color (Cyan, Magenta, Yellow) Maximum Resolution: 5760 x 1440dpi Automatic 2-sided printing: No	2	
14	piece	Wireless microphone with speaker Frequency Range: UHF550-980MHz Total Number of 256 Frequency Points Dynamic Range: 110dB THD: 0.5% Frequency Response: 35Hz to 20 Khz±3dB Signal-to-noise ratio: 90dB Effective Distance:100-150m Transmitter: Transmit power: 10mmW Oscillation mode: PLL digital Frequency Synthesizer Modulation method: FM Image rejection: 50 dB	8	

ROMBLON STATE UNIVERSITY



BIDS AND AWARDS COMMITTEE



				Г
15	set	Desktop	2	
		Processor: 6core 12 threads, 2.90GHz		
		Base Frequency, 4.20GHz Overclocking		
		frequency; Operating System: Windows		
		10; Graphics Card: Integrated Graphics		
		with Shared Memory; Memory: 8GB		
		DDr4 3200Mhz Memory 2 RAM Slots:		
		Storage:500GB SSD; Keyboard:		
		Standard wired USB Keyboard with 10		
		key Number Pad Mouse: Wired USB		
		Laser Mouse; Monitor: 22in Full HD IPS		
		Display (VGA/HDMI)		
16	unit	Printer with ADF (A3 Maximum Size);	2	
10	diffe	32ppm max print speed (Black); 20ppm	_	
		max print speed (Colored)		
17	piece	RAM, 8GB DDR4 3200Mhz	6	
18	unit	UPS, 1500 VA, 1000W	5	
19			3	
	piece	Toner Cartridge, Black, for IM C2000		
20	piece	Toner Cartridge, Magenta, for IM C2000	1	
21	piece	Toner Cartridge, Yellow, for IM C2000	1	
22	piece	Toner Cartridge, Cyan, for IM C2000	1	
23	unit	Orbit Stand Fan; 18-inch blade	2	
		360° oscillating fan		
		Thermal fuse protected motor		
		515x515x390mm		
24	unit	Air conditioner, Split-Type, 2.5Hp, with	1	
		installation; Wattage: 2.27kW (2.5HP);		
		Smart Controller; Full DC Inverter;		
		Energy Efficiency Rating: 13; Cold		
		Plasma Feature; with Multistage		
		Filtration System		
25	piece	Extension Cords (10m 3 sockets)	5	
26	piece	Extension Cords (5m 3 sockets)	5	
27	unit	Stand Fan; 18" diameter, Plastic Blade,	12	
		Push button switch		
28	piece	SSD External Drive 1TB	1	
29	piece	Mouse, wireless	6	
	-	Three buttons in one mouse, With a		
		1600 dpi optical sensor, Ambidextrous		
		design, 2.4GHz Wireless via Nano USB,		
		Mice button-3 (left click, right click,		
		scroll click), Optical Sensor, OS		
		requirements-Windows 7, Windows 8,		
		Windows 8.1, Windows 10, Windows 11		
30	piece	Rechargeable Speaker with Built-in	2	
		Microphone; Portable Speaker with	_	
		built-in rechargeable battery, Bluetooth		
		Wireless Music Streaming, 2 USB		
		inputs for Music Playback, 2		
		microphone inputs, Power Source: AC		
<u> </u>		initiophone inputs, I ower bource. He	<u> </u>	<u> </u>

STATE UNITED TO STATE OF THE ST

ROMBLON STATE UNIVERSITY

BIDS AND AWARDS COMMITTEE





		100-240v 50/60Hz, DC 12V, 4Ah Rechargeable Battery, Output power:		
		60W RMS, Input Terminal: Audio In		
		(Audio Signal): 750V/47K ohms, MIC:		
		, , , , , , , , , , , , , , , , , , , ,		
		600+/-30ohms, Bluetooth Frequency		
0.1		Band: 2.400Ghz-2480Ghz	0	
31	piece	Vacuum Cleaner (wet and dry, 3 gallon),	2	
		Lightweight and Strong, 1100 watts,		
		10ft, 3m power cord, Capacity: 3		
		gallons, Filter Type: Cartridge, Material:		
		ABS Plastic, Standard Accessories:		
		Extension Ward, Floor Nozzle, Crevice		
		Nozzle, and Gulper Nozzle		
32	unit	Heavy Duty Laminating Machine, 13", 4	1	
		Rollers, A3 size		
33	unit	Printer;	1	
		Print, Scan, Copy, Fax with ADF;		
		Printing Technology: Precisioncore™		
		Printhead; Nozzle Configuration: 400 x		
		1 nozzles Black, 128 x 1 nozzles per		
		colour (Cyan, Magenta, Yellow); Print		
		Direction: Bi-directional printing,		
		Maximum Resolution: 4800 x 1200 dpi;		
		Maximum Ink droplet Volume: 3.3 pl.		
34	unit	10.2kg Twin Tub Washing Machine with	1	
		Dryer LWT1020 (H x W x D=94.6cm x	_	
		79.3cm x 46.9cm)		
35	piece	Extension Wire Universal 3-gang (Heavy	2	
	Proce	Duty)		
36	unit	Desktop Computer; Processor:	2	
	arre	10 th Generation (Comet Lake) 8 cores		
		& 16 Threads 2.9 Ghz Clock Speed		
		4.8 Ghz Maximum Turbo Frequency		
		LGA 1200 Socket Dual-Channel		
		DDR4-2933 Memory Intel Optane		
		Memory Support Motherboard: Intel		
		B560 (LGA 1200) PCIe 4.0 two M.2		
		slots 8 power stages Intel 1 Gb		
		Ethernet Display Port Dual HDMI		
		rear USB 3.2 Gen Type-C V-M.2 Key E		
		slot for Wi-Fi Aura Sync Addressable		
		RGB MATX motherboard		
		Memory: 16 GB DDR4 5000 MHz		
		Storage: 500GB SSD Up to 560 MB/s		
		sequential read and 530MB/s write		
		Storage: 500 GB SSD Up to 560 MB/s		
		sequential read and 530 MB/s write		
		GPU: Radeon RX 6500 XT PCI Express		
		4.0 OpenGL®4.6 Video Memory 4GB		
1		GDDR6		

STATE UNITED STATE OF THE PRINTED STATE OF THE PRIN

ROMBLON STATE UNIVERSITY

BIDS AND AWARDS COMMITTEE

Community Outreach Center, RSU-Main Campus, Liwanag, Odiongan, Romblon 5505 Telephone: (042) 567-5952 Email: bac@rsu.edu.ph Website: rsu.edu.ph



		<u></u>		
37	unit	All in One MULTI-FUNCTIONAL	3	
		BORDERLESS PHOTO L850 Printer,		
		Print Method: On-demand ink jet		
		(piezoelectric)		
		Nozzle Configuration: 90 nozzles, each		
		color (Cyan, Light Cyan, Magenta, Light		
		Magenta, Yellow, Black) Print Direction:		
		Bi-direction printing, Unidirectional		
		printing,		
		Maximum Resolution: 5760x1440 dpi		
		(with Variable-sized Droplet Technology)		
		Minimum Ink Droplet Volume: 1.5pl		
38	lot	Airconditioner – 53GCVB013 1.5 Hp. X	2	
		Poer Gold 2 Inverter Split Wall Type		
		Aircon with Installation		
		Technical Supply: 1PH – 230V – 60Hz		
		Capacity: 12,960 (3,312 – 14,760)		
		KJ/HR		
		Power Input: 990 (210 – 1,330) W		
		EER: 13.1 (15.8 – 11.1) KJ/W-HR		
		System Current: 4.9 (1.1 – 6.1) A		
		Sound Level Low: 13dB(A)		
		Refrigerant: R32 or R410A		
		Net Dimension (WxDxH): 798 x 240 x		
		293 mm		
		Packaging (WxDxH): 862 x 280 x 350		
		mm		
		Net/Gross Weight: 9/10Kg		
		Pipe Diameter (Liquid/Gas): 1/4 3/8 inch		
		Max Pipe Height Difference: 12 m		
		Max Pipe Length: 20 m		
39	niece	Exhaust Fan Wall Mount 12 Inches	27	
39	piece	Model: XFW300-12	21	
		Size: 12" Inches		
		Rated Input Power: 50W		
		Rated Voltage: 230V		
		Frequency: 60 Hz		
		Airflow: 18.0m/min		
		Noise Level: 56 dB		
		Case Size: 40.5cm x 14cm x 40.5cm		
		Installation Dimension: 33.5cm x		
		33.5cm		

Name of the Company

Name and Signature of the Bidder/Authorized Representative



ROMBLON STATE UNIVERSITY BIDS AND AWARDS COMMITTEE





ROMBLON STATE UNIVERSITY BIDS AND AWARDS COMMITTEE

