

Community Outreach Center, RSU-Main Campus, Liwanag, Odiongan, Romblon 5505 Telephone: (042) 567-5952 Email: bac@rsu.edu.ph Website: rsu.edu.ph



#### **TECHNICAL SPECIFICATIONS**

Solicitation No. RSU-2023-03-041 ABC: PhP1,752,145.00 QTY: 145

### Procurement of Office and ICT Equipment and Supplies for the ICT Services Center of Romblon State University (Repost)

ITEM NO.	UNIT	ITEM DESCRIPTION	QTY	STATEMENT OF COMPLIANCE
1	unit	High Speed HDMI to HDMI cable digital video with Audio (M/M), Black (15m)	9	
2	unit	Heavy Duty Laminating Machine (13", 4 Rollers, A3 size) Heavy Duty Laminating Machine (13", 4 Rollers, A3 size) Pre-heating time 4-5min, Max width: 330mm, Max Thickness 1mm, MQ320 – reverse/forward function and cold mounting, MQ320A – reverse/forward function with additional manual function (anti-brown out) and cold mounting	1	
3	unit	Rechargeable Valve Regulated Lead Acid Battery (VRLA); NPW36-12; 12 volts 36 Watts	10	
4	unit	Desktop Computer; Processor:  10th Generation (Comet Lake)   8 cores & 16 Threads   2.9 Ghz Clock Speed   4.8 Ghz Maximum Turbo Frequency   LGA 1200 Socket   Dual-Channel DDR4-2933 Memory   Intel Optane Memory Support  Motherboard: Intel B560 (LGA 1200)   PCIe 4.0   two M.2 slots   8 power stages   Intel 1 Gb Ethernet   Display Port   Dual HDMI   rear USB 3.2 Gen Type-C   V-M.2 Key E slot for Wi-Fi   Aura Sync   Addressable RGB   MATX motherboard Memory: 16 GB DDR4 5000 MHz Storage: 500GB SSD Up to 560 MB/s sequential read and 530MB/s write Storage: 500 GB SSD Up to 560 MB/s sequential read and 530 MB/s write GPU: Radeon RX 6500 XT   PCI Express 4.0 OpenGL®4.6   Video Memory 4GB GDDR6	2	

#### **ROMBLON STATE UNIVERSITY**

BIDS AND AWARDS COMMITTEE



		Casing: Corsair 5000D with 600 watts		
		power supply for fan		
		Keyboard and Mouse: MasterSet		
		MS120		
		Display: at least 19" full HD Display		
		with HDMI, DVI port		
		AVR: 500 watts		
5	Unit	All in One MULTI-FUNCTIONAL	2	
		BORDERLESS PHOTO L850 Printer,		
		Print Method: On-demand ink jet		
		(piezoelectric)		
		Nozzle Configuration: 90 nozzles, each		
		color (Cyan, Light Cyan, Magenta, Light		
		Magenta, Yellow, Black)		
		Print Direction: Bi-direction printing,		
		Unidirectional printing,		
		Maximum Resolution: 5760x1440 dpi		
		(with Variable-sized Droplet Technology)		
		Minimum Ink Droplet Volume: 1.5pl		
6	piece	Wi-Fi Dongle Dual-Band 802.11ac,	5	
		Frequency: 2Ghz		
		Signal Rate: 600Mbps(2.4Ghz),		
		1,300Mbps(5Ghz)		
7	unit	Air Conditioner, 2.5HP Split Type (see	1	
		attachment)		
8	unit	Printer, ADF, color 1.44" LCD	1	
		display,Maximum speed 33 ppm in		
		black and 15 ppm in color (draft)†. Up		
		to 10 ppm in black and 5 ppm in color		
		(ISO), With maximum resolution of		
		1200 x 2400 dpi., Print 100, Borderless		
		printing - 3.5 x 5 inches (9 cm x 13 cm),		
		4 x 6 inches (10 cm x 15 cm). Wireless		
		printing4 - Wi-Fi Direct® and Ethernet		
		for work groups. Dimensions:Open:		
		14.8 x 22.8 x 10 inches (375 x 578 x		
		253 mm)		
		Closed: 14.8 x 13.7 x 9.3 inches (375		
		mm x 347 mm x 237 mm),		
		Weight:11 lb (5 kg) excludes inks and		
		cables		
9	set	Stand Fan Power;	2	
		Consumption (W) 65; Fan Features		
		Oscillating; Fan Blade Materials Metal;		
		Number of Blades: 3; Blade Side		
		(inches): 16		
	1	1	l .	

### **ROMBLON STATE UNIVERSITY**

BIDS AND AWARDS COMMITTEE



10	piece	USB 64 gb Available capacities: 64 GB, Performance/speed: Read speeds up to 80MB/s**  Dimensions: 2.24" x 0.84" x 0.43" (56.8 mm x 21.3 mm x 10.8 mm), Operating temperature: 32° - 113° F (0° - 45° C), Storage temperature: 50° - 158° F (-10° - 70° C)  Compatibility: USB 3.0 and USB 2.0	4	
11	set	Glass board Magnetic Dry Erase 60" W x 48" H, Magnetic Dry Erase (with installation)	2	
12	unit	Printer 3 in 1 Print Method: inkjet (piezoelectric) printer Language: ESC/P-R, ESC/P Raster Nozzle Configuration: 180 x 1 Nozzles Black, 59 x 1nozzles per color (Cyan, Magenta, Yellow) Maximum Resolution: 5760 x 1440dpi Automatic	2	
13	piece	2-sided printing: No Wireless microphone with speaker Frequency Range: UHF550-980MHz Total Number of 256 Frequency Points Dynamic Range: 110dB THD: 0.5% Frequency Response: 35Hz to 20 Khz±3dB Signal-to-noise ratio: 90dB Effective Distance:100-150m Transmitter: Transmit power: 10mmW Oscillation mode: PLL digital Frequency Synthesizer Modulation method: FM Image rejection: 50 dB	8	
14	set	Desktop Processor: 6core 12 threads, 2.90GHz Base Frequency, 4.20GHz Overclocking frequency; Operating System: Windows 10; Graphics Card: Integrated Graphics with Shared Memory; Memory: 8GB DDr4 3200Mhz Memory 2 RAM Slots: Storage:500GB SSD; Keyboard: Standard wired USB Keyboard with 10 key Number Pad   Mouse: Wired USB Laser Mouse; Monitor: 22in Full HD IPS Display (VGA/HDMI)	2	

### ROMBLON STATE UNIVERSITY



BIDS AND AWARDS COMMITTEE



_				
15	unit	Printer with ADF (A3 Maximum Size);	2	
		32ppm max print speed (Black); 20ppm		
		max print speed (Colored)		
16	piece	RAM, 8GB DDR4 3200Mhz	6	
17	unit	UPS, 1500 VA, 1000W	5	
18	piece	Toner Cartridge, Black, for IM C2000	3	
19	piece	Toner Cartridge, Magenta, for IM C2000	1	
20	piece	Toner Cartridge, Yellow, for IM C2000	1	
21	piece	Toner Cartridge, Cyan, for IM C2000	1	
22	unit	Orbit Stand Fan; 18-inch blade	2	
		360° oscillating fan		
		Thermal fuse protected motor		
		515x515x390mm		
23	unit	Air conditioner, Split-Type, 2.5Hp, with	1	
		installation; Wattage: 2.27kW (2.5HP);		
		Smart Controller; Full DC Inverter;		
		Energy Efficiency Rating: 13; Cold		
		Plasma Feature; with Multistage		
		Filtration System		
24	piece	Extension Cords (10m 3 sockets)	5	
25	piece	Extension Cords (5m 3 sockets)	5	
26	unit	Stand Fan; 18" diameter, Plastic Blade,	12	
		Push button switch		
27	piece	SSD External Drive 1TB	1	
28	piece	Mouse, wireless	6	
		Three buttons in one mouse, With a		
		1600 dpi optical sensor, Ambidextrous		
		design, 2.4GHz Wireless via Nano USB,		
		Mice button-3 (left click, right click,		
		scroll click), Optical Sensor, OS		
		requirements-Windows 7, Windows 8,		
		Windows 8.1, Windows 10, Windows 11		
29	piece	Rechargeable Speaker with Built-in	2	
		Microphone; Portable Speaker with		
		built-in rechargeable battery, Bluetooth		
		Wireless Music Streaming, 2 USB		
		inputs for Music Playback, 2		
		microphone inputs, Power Source: AC		
		100-240v 50/60Hz, DC 12V, 4Ah		
		Rechargeable Battery, Output power:		
		60W RMS, Input Terminal: Audio In		
		(Audio Signal): 750V/47K ohms, MIC:		
		600+/-30ohms, Bluetooth Frequency		
		Band: 2.400Ghz-2480Ghz	_	
30	piece	Vacuum Cleaner (wet and dry, 3 gallon),	2	
		Lightweight and Strong, 1100 watts,		
		10ft, 3m power cord, Capacity: 3		
		gallons, Filter Type: Cartridge, Material:		
		ABS Plastic, Standard Accessories:		
		Extension Ward, Floor Nozzle, Crevice		
		Nozzle, and Gulper Nozzle		

### **R** B I

### **ROMBLON STATE UNIVERSITY**

BIDS AND AWARDS COMMITTEE





31	unit	Heavy Duty Laminating Machine, 13", 4 Rollers, A3 size Heavy Duty Laminating Machine (13", 4 Rollers, A3 size) Preheating time 4-5min, Max width: 330mm, Max Thickness 1mm, MQ320 – reverse/forward function and cold mounting, MQ320A – reverse/forward function with additional manual function (anti-brown out) and cold mounting	1	
32	unit	Printer; Print, Scan, Copy, Fax with ADF; Printing Technology: Precisioncore™ Printhead; Nozzle Configuration: 400 x 1 nozzles Black, 128 x 1 nozzles per colour (Cyan, Magenta, Yellow); Print Direction: Bi-directional printing, Maximum Resolution: 4800 x 1200 dpi; Maximum Ink droplet Volume: 3.3 pl.	1	
33	unit	10.2kg Twin Tub Washing Machine with Dryer LWT1020 (H x W x D=94.6cm x 79.3cm x 46.9cm)	1	
34	piece	Extension Wire Universal 3-gang (Heavy Duty) 6 meters no.12 flat cord	2	
35	unit	Desktop Computer; Processor:  10th Generation (Comet Lake)   8 cores & 16 Threads   2.9 Ghz Clock Speed   4.8 Ghz Maximum Turbo Frequency   LGA 1200 Socket   Dual-Channel   DDR4-2933 Memory   Intel Optane   Memory Support Motherboard: Intel   B560 (LGA 1200)   PCIe 4.0   two M.2   slots   8 power stages   Intel 1 Gb   Ethernet   Display Port   Dual HDMI   rear USB 3.2 Gen Type-C   V-M.2 Key E   slot for Wi-Fi   Aura Sync   Addressable   RGB   MATX motherboard   Memory: 16 GB DDR4 5000 MHz   Storage: 500GB SSD Up to 560 MB/s   sequential read and 530MB/s write   Storage: 500 GB SSD Up to 560 MB/s   sequential read and 530 MB/s write   GPU: Radeon RX 6500 XT   PCI Express   4.0 OpenGL®4.6   Video Memory 4GB   GDDR6	2	

# STATE UNITED STATE OF STATE OF

#### **ROMBLON STATE UNIVERSITY**

BIDS AND AWARDS COMMITTEE



26	!4	A11 : O MIII WI DIINIOWIONIAI	2	
36	unit	All in One MULTI-FUNCTIONAL	3	
		BORDERLESS PHOTO L850 Printer,		
		Print Method: On-demand ink jet		
		(piezoelectric)		
		Nozzle Configuration: 90 nozzles, each		
		color (Cyan, Light Cyan, Magenta, Light		
		Magenta, Yellow, Black) Print Direction:		
		Bi-direction printing, Unidirectional		
		printing,		
		Maximum Resolution: 5760x1440 dpi		
		(with Variable-sized Droplet Technology)		
		Minimum Ink Droplet Volume: 1.5pl		
37	lot	Airconditioner – 53GCVB013 1.5 Hp. X	2	
		Poer Gold 2 Inverter Split Wall Type		
		Aircon with Installation		
		Technical Supply: 1PH - 230V - 60Hz		
		Capacity: 12,960 (3,312 – 14,760)		
		KJ/HR		
		Power Input: 990 (210 – 1,330) W		
		EER: 13.1 (15.8 – 11.1) KJ/W-HR		
		System Current: 4.9 (1.1 – 6.1) A		
		Sound Level Low: 13dB(A)		
		Refrigerant: R32 or R410A		
		Net Dimension (WxDxH): 798 x 240 x		
		293 mm		
		Packaging (WxDxH): 862 x 280 x 350		
		mm		
		Net/Gross Weight: 9/10Kg		
		Pipe Diameter (Liquid/Gas): ¼ 3/8 inch		
		Max Pipe Height Difference: 12 m		
		Max Pipe Length: 20 m		
38	piece	Exhaust Fan Wall Mount 12 Inches	27	
		Model: XFW300-12		
		Size: 12" Inches		
		Rated Input Power: 50W		
		Rated Voltage: 230V		
		Frequency: 60 Hz		
		Airflow: 18.0m/min		
		Noise Level: 56 dB		
		Case Size: 40.5cm x 14cm x 40.5cm		
		Installation Dimension: 33.5cm x		
		33.5cm		





Name of the Company
Name and Signature of the Bidder/Authorized Representative



Community Outreach Center, RSU-Main Campus, Liwanag, Odiongan, Romblon 5505 Telephone: (042) 567-5952 Email: bac@rsu.edu.ph Website: rsu.edu.ph



Item #7

#### **AIRCON**

#### **Specifications:**

- Split Type, Self Clean + Hyper Pcb 63% Energy Saving
   Hyper Pcb,130~264V Operation
- Dimension: Indoor LxWxH: 22.5cm x 100.8cm x 31.8cm
   Outdoor LxWxH: 33.8cm x 82cm x 55.3cm
- Color: WhiteSize: 2.5 HP



Community Outreach Center, RSU-Main Campus, Liwanag, Odiongan, Romblon 5505 Telephone: (042) 567-5952 Email: bac@rsu.edu.ph Website: rsu.edu.ph



### Item # 11 and # 12

Glass board Magnetic Dry Erase 60"W x 48" H



#### Printer 3 in 1

Print Method: inkjet (Piezoelectric)Printer
Language:ESC/P-R,
ESC/P RasterNozzle
Configuration:180 x 1
nozzles Black, 59 x 1
nozzles per Colour (Cyan, Magenta,
Yellow)Maximum
Resolution:5760 x 1440
dpiAutomatic 2-sided
Printing:No

Photo Default - 10 x 15 cm / 4 x 6 " \*1:Approx. 69 sec per photo (Border) / 90 sec per photo (Borderless)\*2Draft, A4 (Black / Colour):Up to 33.0 ppm / 15.0 ppm\*2ISO 24734, A4 Simplex (Black / Colour):Up to 10.0 ipm / 5.0 ipm\*2First Page Out Time from Ready Mode

Frequency Modulation: 75Hz
Channel conversion mode: touch switch / infrared frequency synchronization
Voltage: 3V DC (2 AA batteries)
Receiver:

Sensitivity: 2.0uV

1.5 °



Community Outreach Center, RSU-Main Campus, Liwanag, Odiongan, Romblon 5505 Telephone: (042) 567-5952 Email: bac@rsu.edu.ph Website: rsu.edu.ph



### Item #13

Oscillation mode: PLL digital Frequency Synthesizer Signal-to-noise ratio: 90dB Distortion: 0.5% Channel conversion mode: touch switch buttons Outputs: 4 balanced output, a 6.35-mixed output Output Voltage: balanced output: 500mV, mixed output: 350mV (30kHz modulation) Power: 110-240V, 50-60Hz (for both USA and Europe standard) Receiver size: 420 × 190 × 44mm, standard 19inch 1U rack mount

### Wireless Microphone with speaker

Frequency range: UHF550-

Total number of 256

980MHz

frequency points
Dynamic range: 110dB
THD: 0.5%
Frequency response: 35Hz
to 20KHz ± 3dB
Signal-to-noise ratio: 90dB
Effective distance: 100150M
Transmitter:
Transmit power:
10mmW
Oscillation mode: PLL
digital Frequency
Synthesizer
Modulation method:

Image rejection: 50dB






Community Outreach Center, RSU-Main Campus, Liwanag, Odiongan, Romblon 5505 Telephone: (042) 567-5952 Email: bac@rsu.edu.ph Website: rsu.edu.ph



### Item #15



Printer Type	Print, Scan, Copy, Fax with ADF
Printing	
Nozzle Configuration	800 x 1 nozzles Black, 256 x 1 nozzles per colour (Cyan,
	Magenta, Yellow)
Print Direction	Bi-directional printing
Maximum Resolution	4800 x 2400 dpi
Minimum Ink Droplet Volume	3.8 pl
Print Speed*1	
Draft Text - Memo, A4 (Black#1 / Colour#2)	Up to 32.0 ppm / 22.0 ppm
ISO 24734, A4 (Black / Colour)	Simplex: Up to 25.0 ipm / 12.0 ipm   Duplex: Up to 16.0 ipm / 9.0 ipm
ISO 24734, A3 (Black / Colour)	Simplex: Up to 13.5 ipm / 6.0 ipm   Duplex: Up to 10.0 ipm / 5.0 ipm
First Page Out Time (Black / Colour), A4	Simplex: Up to 5.5 sec / 8.5 sec   Duplex: Up to 11 sec / 17
	sec
Photo Default - 10 x 15 cm / 4 x 6" *2 #3	Approx. 43 sec per photo (Border) / 52 sec per photo
(Border / Borderless)	(Borderless)
Printer Language	ESC/P-R, ESC/P Raster
Automatic 2-sided printing	Yes (Up to A3)
Copying	
Copy Speed	
ISO 29183, A4 (Black / Colour), Flatbed	Simplex: Up to 23.0 ipm / 10.0 ipm
ISO 24735, A4 (Black / Colour), ADF	Simplex: Up to 22.5 ipm / 10.0 ipm   Duplex: Up to 15.5 ipm
	/ 7.5 ipm
Maximum Copies from Standalone	999 copies
Reduction/Enlargement	25 - 400%
Maximum Copy Resolution	600 x 600 dpi
Maximum Copy Size	A3



Community Outreach Center, RSU-Main Campus, Liwanag, Odiongan, Romblon 5505 Telephone: (042) 567-5952 Email: bac@rsu.edu.ph Website: rsu.edu.ph



### Item #15 (continuation)

Scanning	
Scanner Type	Flatbed colour image scanner
Sensor Type	CIS
Optical Resolution	1200 x 2400 dpi
Maximum Scan Area	297 x 431.8 (mm)
Scanner Bit Depth	
Colour	48-bit input, 24-bit output
Grayscale	16-bit input, 8-bit output
Black & White	16-bit input, 1-bit output
Scan Speed (Flatbed / ADF)	, , , , , , , , , , , , , , , , , , , ,
Monochrome 200dpi	Flatbed: 5 sec   ADF (Simplex / Duplex): Up to 26.0 ipm / 11.5 ipm
Colour 200dpi	Flatbed: 10 sec   ADF (Simplex / Duplex): Up to 9.0 ipm / 6.0 ipm
ADF Function	
Support Paper Thickness	64-95 g/m2
Paper Capacity	50 sheets
Paper Handling	
Paper Feed Method	Friction Feed
Number of Paper Trays	3 (Front 2, Rear 1)
Paper Hold Capacity	
Input Capacity	Cassette 1: 250 sheets for A4 Plain paper (80 g/m2), 50 sheets for Premium Glossy Photo Paper Cassette 2: 250 sheets for A4 Plain paper (80 g/m2) Rear Slot: 50 sheets for A4 Plain paper (80 g/m2), 20 sheets for Premium Glossy Photo Paper
Output Capacity	125 sheets for A4 Plain paper (80 g/m2), 20 sheets for Premium Glossy Photo Paper
Paper Size	A3, Super B (13 x 19"), Indian Legal, Letter, A4, 16K (195 x 270mm), 8K (270 x 390mm), Executive (7.25 x 10.5"), B4, B5, A5, B6, A6, 8.5 x 13", 5 x 7", 4 x 6", 8 x 10", Legal (8.5 x 14"), 16:9 wide, Envelopes: #10, DL, C6, C4
Maximum Paper Size	329 x 6000mm
Print Margin	3mm top, left, right, bottom via custom settings in printer driver
Electrical Specifications	
Rated Voltage	AC 220 - 240 V
Rated Frequency	50 - 60 Hz
Power Consumption	
Operating	19.0 W
Standby	9.1 W
Sleep	0.8 W
Power off	0.2 W



Community Outreach Center, RSU-Main Campus, Liwanag, Odiongan, Romblon 5505 Telephone: (042) 567-5952 Email: bac@rsu.edu.ph Website: rsu.edu.ph



# Item #32

Printer Type	Print, Scan, Copy, Fax with ADF
Printing	
Printing Technology	PrecisionCorer* Printhead
Nozzle Configuration	400 x 1 nozzles Black, 128 x 1 nozzles per colour (Cyan, Magenta, Yellow)
Print Direction	Bi-directional printing
Majornum Resolution	4800 x 1200 dpi
Minimum trik Droplet Volume	3,3 pl
Print Speed	
Draft Text - Memo, A4 (Black* / Colour*)	Up to 38.0 ppm / 24.0 ppm
ISO 24734, A4 (Black / Colour)	Simplified Up to 17.0 ipm / 9.0 ipm   Duplied Up to 7.0 ipm / 5.0 ipm
ISO 24734, A3 (Black Colour)	Smplex, Up to 3.5 pm / 2.3 pm
First Page Out Time (Black / Colour), A4	Simplex: Up to 10 sec / 16 sec   Duplex: Up to 17 sec / 25 sec.
Photo Default - 10 x 15 cm / 4 x 6" 3" (Border / Borderless)	Approx. 71 sec per photo (Borden / 95 sec per photo (Borderless)
Printer Language	ESC / P-R
Automatic 2-sided printing	Yes (up to A4 / Letter)
Copying	
Copy Speed	
ISO 29183, A4 (Black / Colour)	Simplex: Up to 11.5 ipm / 5.5 ipm
Maximum Copies from Standalone	99 copies
Reduction / Enlargement	25 - 400%
Maximum Copy Resolution	600 x 600 dp
Maximum Copy Size	Ligit
canning	
canner Type	Flatbed colour image scanner
ensor Type	OS
ptical Resolution	1200 x 2400 dps
faximum Scan Area	216 x 396 (mm)
canner Bit Depth	
Golour	48-bit input, 24-bit output
Grayscak	16-bit input, 8-bit output
Black & White	16-bit input, 1-bit output
can Speed (Flatbed / ADF (Simplexi)	
Monochrome 200api	Flatbed; 13 sec./ ADF: Up to 5.0 ipm
Colour 200dpi	Flatbed: 28 sec / ADF: Up to 5.0 ipm
ax Function	
ype of Fax	Walk-up Black-and-white and Colour Fax Capability
ecoive Memory - Page Memory	1.1MB, Page memory up to 100 pages
rror Correction Mode	TU-T 1:30
AX Speed (Data Transfer Rate)	Up to 33.6 kbps, Approx. 3 sectpage
AX Resolution	Up ta 200 x 200 dps
ransmission Paper Size	
Flathed	BS, AS, A4, Letter, Logal
ADF	A4, Letter, Legal
eceving Paper Size	B5, B4, A5, A4, Letter, Lugal, A3
peed Dial / Group Dial	Up to 100 numbers, 99 groups
ax Foatures	PC Fax (Transmission / Receive). Automatic Redial. Address book, Broadcast Fax (Mono Only).
AND ADDRESS OF	Transmit Reservation, Polling Reception, Fax Preview
DF Function	



Noise Level

#### ROMBLON STATE UNIVERSITY BIDS AND AWARDS COMMITTEE

Community Outreach Center, RSU-Main Campus, Liwanag, Odiongan, Romblon 5505 Telephone: (042) 567-5952 Email: bac@rsu.edu.ph
Website: rsu.edu.ph



Item #32 (continuation)

Paper Handling	
Paper Feed Method	Friction Feed
Number of Paper Travs	2 (Front 1, Rear 1)
Paper Hold Capacity	Z (FRONT 1, Helse 1)
Input Capacity	
rigical Caspaninty	Classette: 250 sheets for A4 Plan Paper (80 g/m²), 20 sheets for Premium Glossy Photo Paper,
0.4-4.0	Rear Soft 20 sheets for A3+ Plain Paper (80 g/m²)
Output Capacity	30 shoots for A4 Plain Paper (80 g/m²), 20 shoots for Premium Glossy Photo Paper
Paper Size	A3, A3+, Super B, US B (11 x 17"), Legal, Indian Lagal, Letter, A4, 16K (195 x 270mm), 8K (270 x 390mm).
	Executive, B4, B5, A5, B6, A6, Hagale (100 x 148mm), Mexico-Oficio, 8,5 x 131, Office9, Haif-Letter,
	5 x 7", 4 x 6", 8 x 10", 11 x 14", 16-9 wide, Envelopes: 910, DL, C6, C4
Maximum Paper Size	329 x 1200mm
Print Margin	ümm top, left, right, bottom via oustom setting in printer driver (except plain paper) **
Interface	
USB	USB 2.0
Network	Ethernot, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct
Network Protocal	TCP/IPV6, TCP/IPV6
Network Management Protocols	SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, HIDNS, SLP, WSD, LLTD
Mobile and Cloud Printing	
Epson Connect	Epson Print, Epson Email Print, Remote Print Driver, Scan to Cloud
Other Mobile Solutions	Apple AirPrint, Mopris Print Service
Control Panel	
LCD Screen	2.7" Colour LCD Touch Screen
Printer Software	
Software-Support	Epison ScanSmart
Operating System Compatibility	Windows XP / Vista / 7 / 8 / 8 / 1 / 10
	Windows Server 2003 / 2008 / 2012 / 2016 / 2019
	Mac OS X 10 6.8 or later
Electrical Specifications	
Rated Voltage	AC 220 - 240 V
Rated Frequency	50 60 Hz
Power Consumption	
Operating	12.0 W
Standby	5.4 W

Page Yield <sup>3</sup>

Order Code