

Price Schedule for Goods Offered from Within the Philippines
[shall be submitted with the Bid if bidder is offering goods from within the Philippines]

For Goods Offered from Within the Philippines

Name of Bidder _____ Project ID No. RSU 2023-06-054 Page ___ of ___

1	2	3	4	5	6	7	8	9	10
Item	Description	Country of origin	QTY	Unit price EXW per item	Transportation and all other costs incidental to delivery, per item	Sales and other taxes payable if Contract is awarded, per item	Cost of Incidental Services, if applicable, per item	Total Price, per unit (col 5+6+7+8)	Total Price delivered Final Destination (col 9) x (col 4)
1	Laptop: AN 515-45 R5RJ, r9 5900HX, rtx 3070, 16 gb, 512gb ssd, 15.6" 144 hz, w11 (see attachment for specifications)		1						
2	External Drive External Hard Drive HDD 5TB (see attachment for specifications)		1						
3	A3 Printer: Print, Scan, Copy, Fax with ADF, All-in-One Ink Tank Printer (see attachment for		1						

	specifications)								
4	Ink: Epson Pigment Ink #008 (C,M,Y,K) (3bottles/color)		12 bottles						
5	Bond Paper: A4 100GSM		5 reams						
6	A4 Rough Satin		10 packs						
7	Printer (All-in-One Functions: Print, Scan, Copy) Printing Method: PrecisionCore™ Print Head Nozzle Configuration: 400 Nozzles Black, 128 Nozzles per Color Minimum Droplet Size: 3,3 pl, With Variable-Sized Droplet Technology Ink Technology: Pigment ink Printing Resolution: 4.800 x 1.200 DPI Number of Colours: 4 colour Colours: Black [Pigment], Cyan [Pigment], Yellow		45 set						

	<p>[Pigment], Magenta [Pigment] Panel: Color, Touchscreen, Diagonal: 6,1 cm Compatible Operating Systems: Mac OS X 10.6.8 or later, Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Vista, Windows XP, XP Professional x64 Edition Interfaces: WiFi, USB, Ethernet, Wi-Fi Direct WLAN Security: WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP), WPA PSK (AES) Mobile and Cloud Printing services: iPrint, Email Print, Remote Print Driver, Scan-to- Cloud), Apple AirPrint Scan Output formats: BMP, JPEG, PICT, TIFF, multi-TIFF, PDF, PNG Scanner Type: Contact Image Sensor (CIS) Optical Resolution: 1.200 DPI x 2.400 DPI (Horizontal x Vertical)</p>									
8	Dual Professional		10 set							

	<p>Wireless Microphone ACT 9090U System</p> <ul style="list-style-type: none"> • Frequency Range: UHF 500 Mhz ~ 900 MHz • Modulation Mode: FM (PLL) • Frequency Deviation: ± 25 kHz/± 48 kHz • Frequency Stability: ± 15ppm • Signal-to-Noise Ratio: 110 Db(A) • T.H.D : 1% • Operating temperature: - $10^{\circ}\text{c} \sim +55^{\circ}\text{c}$ Receiver • Sensitivity (peak deviation) : 3uV(52dB S/N) • AF output clipping level : • Balanced Outputs: +10dB 												
--	---	--	--	--	--	--	--	--	--	--	--	--	--

	<p>(XLR)</p> <ul style="list-style-type: none">• Unbalanced outputs: +4dB (1/4" 6.33mm jack socket)• Adjacent channel interface ratio: 80 dB• Image interference Ratio: 80 dB Transmitter• RF Outputs: 8mW~30mW• Harmonic Suppression >50 dB• AF output clipping level :• Balanced Outputs: +10dB (XLR)• Unbalanced outputs: +4dB (1/4" 6.33mm jack socket)• Adjacent channel interface ratio:								
--	---	--	--	--	--	--	--	--	--

	80 dB <ul style="list-style-type: none"> • Image interference Ratio: 80 dB Transmitter • RF Outputs: 8mW~30mW Harmonic Suppression >50 dB								
9	Memory DDR4 - 8gb 3200Mhz RGB HyperX Fury CL16 DIMM		20 piece						
10	Solid State Drive 480GB A400 Sata3 2.5-inch		30 piece						
11	Heat Gun D26411 with Rotary Air Temperature Dial (1,800W) with 2 extra nozzle		1 piece						
12	Blower/Vacuum cleaner Powerful motor with High Volume of 3500I MIN		1 piece						
13	RJ45 Passthrough Connectors for CAT5E CAT6 LAN Cables (100pcs/box)		5 box						
14	HDMI Extender cat5 60M 120M HDMI		8 pair						

	Extender audio kit over Ethernet cat6/5e for PS4 apple TV PC laptop HDTV								
15	HDMI 2.0v Optical Fiber cable (50 meters)		8 piece						
16	UTP Cable Cat 6 Outdoor (305m/roll)		1 box						
17	Cleaning Solution for Inkjet Printer and Syringe with Hose 100 ml		15 bottles						
18	Heat Shrink Tubing Insulation Shrinkable Tube Assortment 580 pcs with box		2 box						
19	RJ45 Rubber Boot 100 pcs/pack (Blue)		5 pack						
20	Thermal Conductive Grease Paste for Processor CPU Heat Sink Plaster (5g)		15 Syringe						
21	UPS SRV 2000VA 230V, 1600 Watts		2 piece						
22	Active Speaker System: System Type: Passive 18", subwoofer		6 piece						

	<p>system</p> <p>Maximum SPL Output: 135 Db</p> <p>Frequency Range(- 10Db): 28Hz – 150 Hz</p> <p>Frequency Response (-3 Db): 45Hz-150 Hz</p> <p>System Power Rating: 2400W Peak, 1200W Program, 600W Continous</p> <p>Nominal Impedance: 8 Ohm Connectors: NL4 Input, NL4 Loop-thru (+/-1 or +/-2 Selectable)</p> <p>Operational Modes: Passive</p> <p>LF Driver: 2279H</p> <p>Crossover Frequency: 80Hz</p> <p>Material: 18mm plywood</p> <p>Suspension/Mounting: M20 Threaded Pole Mount</p> <p>Handles: 4</p> <p>Finish: Obsidian Duraflex™ Finish</p> <p>Grille: Powder Coated, Onsidian 14 gauge perforated steel with acoustically transparent black cloth backing</p> <p>Dimensions (L x W x H):</p>												
--	---	--	--	--	--	--	--	--	--	--	--	--	--

	26.89" x 26.92" x 22.62" (683mm x 684mm x 575mm)								
23	Microphone Stand Heavy Duty Adjustable and Collapsible Tripod Boom Mic Stand Made of Heavy Duty Sturdy Steel Construction, extra sturdy and durable 2 Arms & 2 Microphone Holders (large arm extends to 52 inches, and the small arm offers both extendability and 360° rotation)		10 piece						
24	XLR 3 pin Plug Microphone Audio Cable Wire Connector (Male/Female)		10 pair						
25	DSLR Camera EOS 80D DSLR Camera w/ 18-135mm Lens 24.2MP PS-C CMOS Sensor DIGIC 6 Image Processor 3.0" 1.04m-Dot Vari- Angle Touchscreen LCD		10 set						

	<p>Full HD 1080p60 45-Point All Cross-Type AF System Dual Pixel CMOS AF Expanded ISO 25600, Up to 7fps Shooting Built-in WiFi with NFC</p>								
26	<p>Projector Projection System: 3LCD LCD Panel: 0.55-inch Light Source: Lamp Resolution: XGA Color Light Output: 4,100 Lumens White Light Output: 4,100 Lumens Native Aspect Ratio: 4:3 Contrast Ratio: 16,000:1 Lamp Type: 230 W UHE Keystone Correction: Vertical: -30to +30 degrees Horizontal: -30 to +30 degrees; Zoom:1-1.6 (Optical); Screen Size (Standard Lens): 27" to 262"; Projection Distance (Standard Lens): 27" to 262"; Projection Distance (Standard Lens): 60"</p>		10 set						

<p> screen 1.93 – 3.14m; Throw Ratio: 1.58 (Zoom: Wide); 2.56 (Zoom: Tele) Projection Lens F Number: 1.51 – 1.99; Projection Lens Focal Length: 18.2 mm – 29.2mm; Focus Method: Manual; Offset: 19.4:1 Connectivity Input: Video 1 x RCA (Yellow); Input: Computer 2 x D-sub 15- Pin (RGB) 1 x USB 2.0 type B; Input: Digital 2 x HDMI; Input: Audio 2 x RCA (Red/White); 2 x Stereo mini; Control: I/O 1 x RS232C; Network: I/O 1 x RJ45 1 x USB 2.0 type A (for optional Wireless LAN); Output: Video 1 x D- sub 15 pin; Output: Audio 1 x stereo mini; Built-in Speaker 16w; Miracast-Split Screen; Auto Keystone Correction Vertical: -30 to +30 degrees Horizontal Slide Keystone Correction </p>												
---	--	--	--	--	--	--	--	--	--	--	--	--

	Yes; Colour Modes: Dynamic, Presentation, Cinema, sRGB, Blackboard; Projector Warranty 3 years.								
TOTAL			258						

Name: _____

Legal Capacity: _____

Signature: _____

Duly authorized to sign the Bid for and behalf of: _____