ROMBLON STATE UNIVERSITY BIDS AND AWARDS COMMITTEE Community Outreach Center, RSU-Main Campus, Liwanag, Odiongan, Romblon 5505 Telephone: (042) 567-5952 Email: bac@rsu.edu.ph Website: rsu.edu.ph



TECHNICAL SPECIFICATIONS

Solicitation No. RSU-2023-06-054 ABC: PhP3,391,650.00 QTY: 258

Procurement of ICT Equipment and Supplies for the Different Units of Romblon State University

Rombion State University				
ITEM NO.	UNIT	ITEM DESCRIPTION	QTY	STATEMENT OF COMPLIANCE
1	unit	Laptop: AN 515-45 R5RJ, r9 5900HX, rtx 3070, 16 gb, 512gb ssd, 15.6" 144 hz, w11 (see attachment for specifications)	1	
2	unit	External Drive External Hard Drive HDD 5TB (see attachment for specifications)	1	
3	unit	A3 Printer: Print, Scan, Copy, Fax with ADF, All-in-One Ink Tank Printer (see attachment for specifications)	1	
4	bottles	Ink: Epson Pigment Ink #008 (C,M,Y,K) (3bottles/color)	12	

ROMBLON STATE UNIVERSITY

BIDS AND AWARDS COMMITTEE





5	reams	Bond Paper: A4 100GSM	5	
6	Packs	A4 Rough Satin Paper	10	
7	set	Printer (All-in-One Functions: Print, Scan, Copy) Printing Method: PrecisionCore™ Print Head Nozzle Configuration: 400 Nozzles Black, 128 Nozzles per Color Minimum Droplet Size: 3,3 pl, With Variable-Sized Droplet Technology Ink Technology: Pigment ink Printing Resolution: 4.800 x 1.200 DPI Number of Colours: 4 colour Colours: Black [Pigment], Cyan [Pigment], Yellow [Pigment], Magenta [Pigment] Panel: Color, Touchscreen, Diagonal: 6,1 cm Compatible Operating Systems: Mac OS X 10.6.8 or later, Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Vista, Windows XP, XP Professional x64 Edition Interfaces: WiFi, USB, Ethernet, Wi-Fi Direct WLAN Security: WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP), WPA PSK (AES) Mobile and Cloud Printing services: iPrint, Email Print, Remote Print Driver, Scan-to-Cloud), Apple AirPrint Scan Output formats: BMP, JPEG, PICT, TIFF, multi-TIFF, PDF, PNG Scanner Type: Contact Image Sensor (CIS) Optical Resolution: 1.200 DPI x 2.400 DPI (Horizontal x Vertical)	45	

STATE UNITED STATE

ROMBLON STATE UNIVERSITY

BIDS AND AWARDS COMMITTEE



8	piece	Dual Professional Wireless Microphone ACT 9090U System Frequency Range: UHF 500 Mhz 900 MHz Modulation Mode: FM (PLL) Frequency Deviation: ±25 kHz/?±48 kHz Frequency Stability: ±15ppm Signal-to-Noise Ratio: 110 Db(A) T.H.D: 1% Operating temperature: -10°c ~ +55°c Receiver Sensitivity (peak deviation): 3uV(52dB S/N) AF output clipping level: Balanced Outputs: +10dB (XLR) Unbalanced outputs: +4dB (1/4" 6.33mm jack socket) Adjacent channel interface ratio: 80 dB Image interference Ratio: 80 dB Transmitter RF Outputs: 8mW~30mW Harmonic Suppression >50 dB AF output clipping level: Balanced Outputs: +10dB (XLR) Unbalanced outputs: +4dB (1/4" 6.33mm jack socket) Adjacent channel interface ratio: 80 dB Image interference Ratio: 80 dB Transmitter RF Outputs: 8mW~30mW Harmonic Suppression >50 dB Memory DDR4 - 8gb 3200Mhz RGB	20	
	-	HyperX Fury CL16 DIMM		
10	piece	Solid State Drive 480GB A400 Sata3 2.5-inch	30	

ROMBLON STATE UNIVERSITY

BIDS AND AWARDS COMMITTEE



11	piece	Heat Gun D26411 with Rotary Air Temperature Dial (1,800W) with 2 extra nozzle	1	
12	piece	Blower/Vacuum cleaner Powerful motor with High Volume of 3500I/MIN	1	
13	box	RJ45 Passthrough Connectors for CAT5E CAT6 LAN Cables (100pcs/box)	5	
14	pair	HDMI Extender cat5 60M 120M HDMI Extender audio kit over Ethernet cat6/5e for PS4 apple TV PC laptop HDTV	8	
15	piece	HDMI 2.0v Optical Fiber cable (50 meters)	8	
16	box	UTP Cable Cat 6 Outdoor (305m/roll)	4	
17	bottle	Cleaning Solution for Inkjet Printer and & Syringe with Hose 100 ml	15	
18	box	Heat Shrink Tubing Insulation Shrinkable Tube Assortment 580 pcs with box	2	
19	pack	RJ45 Rubber Boot 100 pcs/pack (Blue)	5	
20	Syrin ge	Thermal Conductive Grease Paste for Processor CPU Heat Sink Plaster (5g)	15	
21	piece	UPS SRV 2000VA 230V, 1600 Watts	2	

STATE UNIVERSITY 1915 ANTI-PPINST

ROMBLON STATE UNIVERSITY

BIDS AND AWARDS COMMITTEE



22	piece	Active Speaker System: System Type: Passive 18", subwoofer system Maximum SPL Output: 135 Db Frequency Range(-10Db): 28Hz − 150 Hz Frequency Response (-3 Db): 45Hz- 150 Hz System Power Rating: 2400W Peak, 1200W Program, 600W Continuous Nominal Impedance: 8 Ohm Connectors: NL4 Input, NL4 Loop- thru (+/-1 or +/-2 Selectable) Operational Modes: Passive LF Driver: 2279H Crossover Frequency: 80Hz Material: 18mm plywood Suspension/Mounting: M20 Threaded Pole Mount Handles: 4 Finish: Obsidian Duraflex™ Finish Grille: Powder Coated, Onsidian14 gauge perforated steel with acoustically transparent black cloth backing Dimensions (L x W x H): 26.89" x 26.92" x 22.62" (683mm x 684mm x 575mm)	6	
23	piece	Microphone Stand Heavy Duty Adjustable and Collapsible Tripod Boom Mic Stand Made of Heavy Duty Sturdy Steel Construction, extra sturdy and durable 2 Arms & 2 Microphone Holders (large arm extends to 52 inches, and the small arm offers both extendibility and 360° rotation)	10	
24	pair	XLR 3 pin Plug Microphone Audio Cable Wire Connector (Male/Female)	10	

Management System ISO 9001:2015 TÜVRheinla

25	set	DSLR Camera EOS 80D DSLR Camera w/ 18- 135mm Lens 24.2MP PS-C CMOS Sensor DIGIC 6 Image Processor 3.0" 1.04m-Dot Vari-Angle Touchscreen LCD Full HD 1080p60 45-Point All Cross-Type AF System Dual Pixel CMOS AF Expanded ISO 25600, Up to 7fps Shooting Built-in WiFi with NFC	10	

STATE UNITED TO STATE UNITED T

ROMBLON STATE UNIVERSITY

BIDS AND AWARDS COMMITTEE



26	set	Projector	10	
		Projection System: 3LCD		
		LCD Panel: 0.55-inch		
		Light Source: Lamp		
		Resolution: XGA		
		Color Light Output: 4,100 Lumens		
		White Light Output: 4,100 Lumens		
		Native Aspect Ratio: 4:3		
		_		
		Contrast Ratio: 16,000:1		
		Lamp Type: 230 W UHE		
		Keystone Correction: Vertical: -30to		
		+30 degrees		
		Horizontal: -30 to +30 degrees;		
		Zoom:1-1.6 (Optical); Screen Size		
		(Standard Lens): 27" to 262";		
		Projection Distance (Standard Lens):		
		27" to 262"; Projection Distance		
		(Standard Lens): 60" screen 1.93 –		
		3.14m; Throw Ratio: 1.58 (Zoom:		
		Wide); 2.56 (Zoom: Tele)		
		Projection Lens F Number: 1.51 –		
		1.99; Projection Lens Focal Length:		
		18.2 mm – 29.2mm; Focus Method:		
		Manual; Offset: 19.4:1		
		Connectivity		
		Input: Video 1 x RCA (Yellow); Input:		
		Computer2 x D-sub 15-Pin (RGB)		
		1 x USB 2.0 type B; Input: Digital 2 x		
		HDMI; Input: Audio 2 x RCA		
		(Red/White); 2 x Stereo mini; Control:		
		I/O 1 x RS232C; Network: I/O 1 x		
		RJ45		
		1 x USB 2.0 type A (for optional		
		Wireless LAN); Output: Video 1 x D-		
		sub 15 pin; Output: Audio 1 x stereo		
		mini; Built-in Speaker16w; Miracast-		
		Split Screen; Auto Keystone		
		Correction Vertical: -30 to +30 degrees		
		Horizontal Slide Keystone Correction		
		Yes; Colour Modes: Dynamic,		
		Presentation, Cinema, sRGB,		
		Blackboard; Projector Warranty 3		
		years.		
	1			





Name of the Company	_
Name and Signature of the Bidder/Authoriz	ed Representative



Community Outreach Center, RSU-Main Campus, Liwanag, Odiongan, Romblon 5505 Telephone: (042) 567-5952 Email: bac@rsu.edu.ph Website: rsu.edu.ph



Item #1

Laptop

Display

Size: 15.6 inches Type: IPS LCD Refresh rate: 144 Hz PPI: 141 ppi

Aspect ratio: 16:9

Resolution: 1920 x 1080 pixels

Battery

Capacity: 57 Wh Battery type: Li-Ion Fast charging: Yes

Charging port position: Left Charge power: 135 W

CDLI

Base frequency: 3.3 GHz Turbo frequency: 4.2 GHz

Cores: 6 Threads: 12 L3 Cache: 16 MB

Integrated GPU: Radeon RX Vega 7

Fabrication process: 7 nm

Graphics Card TGP: 85 W

Nvidia Optimus: Yes

Type: Dedicated Fabrication process: 8 nm GPU base clock: 855 MHz

GPU boost clock: 1365 MHz FLOPS: 13.9 TFLOPS Memory size: 8 GB Memory type: GDDR6 Memory bus: 256 bit

Memory speed: 12 Gbps Shading units (cores): 5120

Texture mapping units (TMUs): 160 Raster operations pipelines (ROPs): 80

RAM

Channels: 2x8 GB Clock: 3200 MHz Type: DDR4 Upgradable: Yes



Community Outreach Center, RSU-Main Campus, Liwanag, Odiongan, Romblon 5505 Telephone: (042) 567-5952 Email: bac@rsu.edu.ph Website: rsu.edu.ph



Item #1 (confination)

Total slots: 2

Max. ram size: 32 GB

Storage

Bus: PCI-E Gen 3.0 (4x) Storage type: SSD (M2) Channels: 1x512 GB Upgradable: Yes Total slots: 2 NVMe: Yes

Sound

Audio chip: Realtek ALC295

Speakers: 2.0 Dolby Atmos: No Loudness: 75.5 dB Microphones: 2

Connectivity

Wi-Fi standard: v6 Bluetooth: v5

Webcam: Above the display Webcam resolution: 1280 x 720

Ports

USB-A: 3x USB 3.2 USB Type-C: 1x USB 3.2 HDMI: 1x HDMI 2.0 Audio jack (3.5 mm): Yes Ethernet (RJ45): Yes

Proprietary charging port: Yes

Input

Keyboard type: Island

Numpad: Yes Backlight: Yes

Touch Pad Size: 10.6 x 7.8 cm

Surface: Plastic

Windows Precision: Yes



Community Outreach Center, RSU-Main Campus, Liwanag, Odiongan, Romblon 5505 Telephone: (042) 567-5952 Email: bac@rsu.edu.ph Website: rsu.edu.ph



Item #2

External Hard Drive HDD

Digital Storage Capacity: 5 TB Hard Disk Interface: USB 3.0 Connectivity Technology: USB Special Feature: Portable

Hard Disk Form Factor: 2.5 Inches

Hard Disk Description: Mechanical Hard Disk

Compatible Devices: Desktop Installation Type: Plug In



Community Outreach Center, RSU-Main Campus, Liwanag, Odiongan, Romblon 5505 Telephone: (042) 567-5952 Email: bac@rsu.edu.ph Website: rsu.edu.ph



Item #3

A3 Printer

Printer Type:

Print, Scan, Copy, Fax with ADF

Printing Technology:

Print Method: PrecisionCore™ Printhead Minimum Ink Droplet Volume:3.8 pl Print Direction:Bi-directional printing

Nozzle Configuration:800 x 1 nozzles Black, 256 x 1 nozzles per colour (Cyan, Magenta, Yellow)

Maximum Resolution:4800 x 2400 dpi Automatic 2-sided Printing:Yes (up to A3)

Print Speed

Photo Default - 10×15 cm / 4×6 " *1:Approx. 43 sec per photo (Border) / 52 sec per photo (Particles)

Draft, A4 (Black / Colour):Up to 32.0 ppm / 22.0 ppm

ISO 24734, A4 Simplex (Black / Colour): Up to 25.0 ipm / 12.0 ipm

ISO 24734, A4 Duplex (Black / Colour):Up to 16.0 ipm / 9.0 ipm

ISO 24734, A3 Simplex (Black / Colour): Up to 13.5 ipm / 6.0 ipm

ISO 24734, A3 Duplex (Black / Colour):Up to 10.0 ipm / 5.0 ipm