

BIDS AND AWARDS COMMITTEE

Community Outreach Center, RSU-Main Campus, Liwanag, Odiongan, Romblon 5505 Telephone: (042) 567-5952 Email: bac@rsu.edu.ph Website: rsu.edu.ph



BID BULLETIN

Clarification No. 1

Solicitation No.: RSU-2024-09-080

TO

.

All Prospective Bidders

SUBJECT

Change/Modification of the Delivery Schedule, Checklist of Technical and Financial Documents, and Specifications in all attached/associated documents in the Philippine Bidding Documents (PBDs), and Technical

Specifications

DATE

10 October 2024

This Bid Bulletin is issued to inform all prospective bidders of the change/modification of the Delivery Schedule, Checklist of Technical and Financial Documents, and Specifications in all attached/associated documents in the PBDs, and Technical Specifications. Please take notice of these changes.

Supply and Delivery of Coaster - 29+1 Seater (Manual) for Romblon State University (ABC: PhP4,000,000.00)

RE: Delivery Schedule

FROM	TO
Delivery of the Goods is required by within	Delivery of the Goods is required by within sixty
twenty-five (25) calendar days from receipt	(60) calendar days from receipt of the Notice
of the Notice to Proceed.	to Proceed.

RE: Checklist of Technical and Financial Documents

FROM				TO					
(e)	Conformity	with	the	Technical	(e)	Conformity	with	the	Technical
	Specifications,		which	include		Specifications,		which	include
	production/del	ivery	schedule,	manpower		production/del	ivery	schedule,	manpower
	requirements,	and/	or after-	sales/parts;		requirements,	and,	or after-	sales/parts;
	and					and			

RE: Technical Specifications

FROM

NO.	UNIT	ITEM DESCRIPTION	QTY	STATEMENT OF COMPLIANCE ¹
1	unit	COASTER - 29+ 1 SEATER (Manual) OVERALL DIMENSIONS: Length x Width x Height (mm): 6,990 x 2,080 x 2,635 or 7,110 x 2,035 x 2,630 Wheelbase (mm) - 3,935 or 4,085	1	

I [Bidders must state here either "Comply" or "Not Comply" against each of the individual parameters of each Specification stating the corresponding performance parameter of the equipment offered. Statements of "Comply" or "Not Comply" must be supported by evidence in a Bidders Bid and cross-referenced to that evidence. Evidence shall be in the form of manufacturer's un-amended sales literature, unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data etc., as appropriate. A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence presented will render the Bid under evaluation liable for rejection. A statement either in the Bidder's statement of compliance or the supporting evidence that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder or supplier liable for prosecution subject to the applicable laws and issuances.]



BIDS AND AWARDS COMMITTEE

Community Outreach Center, RSU-Main Campus, Liwanag, Odiongan, Romblon 5505 Telephone: (042) 567-5952 Email: bac@rsu.edu.ph Website: rsu.edu.ph



Management System ISO 9001:2015



Tread Front / Rear (mm) – 1,690/1,490 or Manufacturer Standard

Minimum Tire Turning Radius (m): 6.4 or

Manufacturer Standard

Curb Weight (kg) - 3,530 to 4,555

Gross Vehicle Weight (kg) - 5,670 to 6,765

Color: Pearl White or White or Creamy white

ENGINE & TRANSMISSION:

Model - N04C-VQ or D4GA14

Type - 4 Cylinder In-line, 16-Valve OHV or

Turbocharger Intercooler,

4-Stroke cycle, water-cooled, direct injection diesel Engine Displacement: (cc) 3,933 but not exceeding

6,500

Maximum Output (PS/rpm) - 135/2,500 or

140/2,700

Maximum Torque (Nm/rpm) - 390/1,400 or (kg-

m/rpm) - 38/1,600

Fuel Capacity: 95L Diesel

Transmission - 5 Speed Manual or 5 Forward and

1 reverse speed

Fuel System: Common-rail Type or Denso

Common rail system Regulation L: EURO 4

CHASSIS:

Suspension:

Front: Double Wishbone

Rear: Leaf Spring, Rigid with Front and Rear

Stabilizers

Shock Absorber: Hydraulic double-acting telescopic type or manufacturer-standard Steering System - Power Assisted Recirculating Bell or 4 spoke, ball-nut type, Tilt & Telescopic

steering column

Tires and Wheels: Front & Rear: 215/70R17.5 or

205/75R17.5 - 10PR

FEATURES:

Airbags - Driver and Assistant

Fog Lamps - Front: Projector Type

Rear - LH/RH Combination Lamps

Wheel Cover - With Rear Under View Mirror - With

Door Type - Auto Swing Door

Over Head Shelves - With Clock (Roof) - Digital

Room Lamps - Fluorescent Room Lamps, Reading

Lamps & Curtain Rail

Audio System - M850B (Radio + CDP with Mic,

TV, AUX and USB Connectivity) + Speakers: Front

(2ea), Mid (1ea), Rear (1ea)

Air-conditioning - Roof-mounted A/C with Electric





ROMBLON STATE UNIVERSITY BIDS AND AWARDS COMMITTEE

Community Outreach Center, RSU-Main Campus, Liwanag, Odiongan, Romblon 5505 Telephone: (042) 567-5952 Email: bac@rsu.edu.ph Website: rsu.edu.ph



Management System ISO 9001:2015



Brake Control System - Anti-Locking Brake System(ABS)	
Parking Brake - Integral expanding type on propeller shaft at the rear of transmission	
Service Brake - Hydraulic with vacuum servo assistance dual circuit	
Extinguisher	
Seatbelts Front: With Seatbelts Rear: 2.pt Waving Type with Fire	
SAFETY:	
With rear luggage compartment	
Window Wipers: Full-size	
Seat Material: Fabric	
Ventilator (Dual A/C controls with LCD) Seating Capacity - 29+1 (Standard Seats)	



BIDS AND AWARDS COMMITTEE

Community Outreach Center, RSU-Main Campus, Liwanag, Odiongan, Romblon 5505 Telephone: (042) 567-5952 Email: bac@rsu.edu.ph Website: rsu.edu.ph





TO

ITEM				STATEMENT OF
NO.	UNIT	ITEM DESCRIPTION	QTY	COMPLIANCE ²
		COASTER - 29+ 1 SEATER (Manual)		
1	unit	OVERALL DIMENSIONS: Length x Width x Height (mm): 6,990 x 2,080 x 2,635 or 7,110 x 2,035 x 2,630 Wheelbase (mm) - 3,935 or 4,085 Tread Front / Rear (mm) - 1,690/1,490 or Manufacturer Standard Minimum Tire Turning Radius (m): 6.4 or Manufacturer Standard Curb Weight (kg) - 3,530 to 4,555 Gross Vehicle Weight (kg) - 5,670 to 6,765 Color: Pearl White or White or Creamy white ENGINE & TRANSMISSION: Model - N04C-VQ or D4GA14 Type - 4 Cylinder In-line, 16-Valve OHV or Turbocharger Intercooler, 4-Stroke cycle, water-cooled, direct injection diesel Engine Displacement: (cc) 3,933 but not exceeding 6,500 Maximum Output (PS/rpm) - 135/2,500 or 140/2,700 Maximum Torque (Nm/rpm) - 390/1,400 or (kg-m/rpm) - 38/1,600 Fuel Capacity: 95L Diesel Transmission - 5 Speed Manual or 5 Forward and 1 reverse speed	1	
		Fuel System: Common-rail Type or Denso Common rail system Regulation L: EURO 4		
		CHASSIS:		
		Suspension: Front: Double Wishbone		
		Rear: Leaf Spring, Rigid with Front and Rear		
		Stabilizers		
		Shock Absorber: Hydraulic double-acting		
		telescopic type or manufacturer-standard		
		Steering System - Power Assisted Recirculating		
		Bell or 4 spoke, ball-nut type, Tilt & Telescopic		
		steering column		

² [Bidders must state here either "Comply" or "Not Comply" against each of the individual parameters of each Specification stating the corresponding performance parameter of the equipment offered. Statements of "Comply" or "Not Comply" must be supported by evidence in a Bidders Bid and cross-referenced to that evidence. Evidence shall be in the form of manufacturer's un-amended sales literature, unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data etc., as appropriate. A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence presented will render the Bid under evaluation liable for rejection. A statement either in the Bidder's statement of compliance or the supporting evidence that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder or supplier liable for prosecution subject to the applicable laws and issuances.]



BIDS AND AWARDS COMMITTEE





Tires and Wheels: Front & Rear: 215/70R17.5 or 205/75R17.5 - 10PR FEATURES: Airbags - Driver and Assistant Fog Lamps - Front: Projector Type Rear - LH/RH Combination Lamps Wheel Cover - With Rear Under View Mirror - With Door Type - Auto Swing Door Over Head Shelves - With Clock (Roof) - Digital Room Lamps - Fluorescent Room Lamps, Reading Lamps & Curtain Rail Audio System - M850B (Radio + CDP with Mic, TV, AUX and USB Connectivity) + Speakers: Front (2ea), Mid (1ea), Rear (1ea) Air-conditioning - Roof-mounted A/C with Electric Ventilator (Dual A/C controls with LCD) Seating Capacity - 29+1 (Standard Seats) Seat Material: Fabric Window Wipers: Full-size With rear luggage compartment SAFETY: Seatbelts Front: With Seatbelts Rear: 2.pt Waving Type with Fire Extinguisher Service Brake - Hydraulic with vacuum servo assistance dual circuit Parking Brake - Integral expanding type on propeller shaft at the rear of transmission Brake Control System - Anti-Locking Brake System(ABS) With Red plate for vehicle registration Preventive Maintenance Service (PMS) shall be undertaken by the manufacturers, as follows: Free labor, oil and oil filter for the first 5,000 km mileage or three (3) months whichever comes first; and Free labor for the 10,000 km mileage or six

Please be advised that this bid bulletin is issued to amend the Delivery Schedule, Checklist of Technical and Financial Documents, and Specifications in all attached/associated documents. This shall be an integral part of the Bid Documents.

1

(6) months whichever comes first.

TOTAL

For information and guidance of all concerned.

ATTY. GLENN NIÑO M. SARTILLO BAC Chairperson